

DESCRIPTION

Clear Label Protection Tape. Wide tape secures and protects shipping labels. This tape holds well during rough handling during the shipping process. Biaxially Oriented Polypropylene Film (BOPP) with an acrylic adhesive layer.

APPLICATION PROCESS

For covering address labels, packing lists, sales slips and other applications subjected to rough handling or where a high level of performance is required. Excellent transparency making labels clean, legible and attractive. Tape that is tough, clear, and abrasion-resistant. Will hold your label, invoice or packing list securely to a wide variety of surfaces. Conforms to FDA Specs (clear tape only): 21 CFR 175.105 and CFR 177.1520

MATERIAL DESCRIPTION	
SIZE (width x length)	4" x 72 yd
COLOR	Clear
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA	
ADHESIVE LAYER	Acrylic
BACKING/CARRIER MATERIAL	Polypropylene Film (BOPP)
BACKING/ADHESIVE THICKNESS	1.0 mil
TOTAL THICKNESS	1.6 mils PSTC-33
ADHESION TO STEEL	15 oz/in PSTC-1 (180° Peel Adhesion)
TENSILE STRENGTH	20 lbs/in width PSTC-131
ELONGATION	160 max PSTC-131
TEMPERATURE APPLICATION	32°F to 140°F
TEMPERATURE OPERATING	- 10°F to 200°F

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com