

DESCRIPTION

Red Specialty Paper Masking Tape. A conformable/flexible crepe paper coated with a pressure-sensitive natural/synthetic rubber adhesive for versatile performance. For use as a general purpose tape, where the need for colors for coding or identification is desired. Identification & coding, bag sealing/closure (produce, small candy bags, poultry, etc.), coupon book binding. Available in coated colors. Product is not printable.

APPLICATION PROCESS

For use on a variety of substrates as a general purpose tape for labeling, color coding, decorating, identification, packaging, bundling, binding, holding, and banding. Silicone-free tape. Tested according to LHAMA procedures. Applicable standards defined by ASTM D6123/D6123M-07 Type. Meets Consumer Product Safety Commission requirements through conformance with ASTM D-4236

MATERIAL DESCRIPTION	
SIZE (width x length)	1/2" x 60 yd
COLOR	Red
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	N/A
WEIGHT	

TECHNICAL DATA	
ADHESIVE LAYER	Rubber
BACKING/CARRIER MATERIAL	Crepe Paper
BACKING/ADHESIVE THICKNESS	N/A
TOTAL THICKNESS	4.6 mil
ADHESION TO STEEL	32 oz/in width (3.50 N/10mm)
TENSILE STRENGTH	18 lbs/in width (31.5 N/10mm)
ELONGATION	7%
TEMPERATURE APPLICATION	50°F to 150°F (service temp range)
TEMPERATURE OPERATING	

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com