

DESCRIPTION

Barricade Tape. Barricade Warning Tapes consist of high visibility yellow or red three-ply polyethylene with bold black letters. Durable, 3-ply weather resistant polyethylene film with standard 2 inch letters. Easy to read and flexible in below freezing temperatures. CAUTION-CAUTION

APPLICATION PROCESS

The Barricade Warning Tape help prevents accidents by increasing visibility of hazards and can be tied, stapled or nailed in place. Three-ply for added strength. Long roll length, will not tear easily, and designed for both large and small areas.

MATERIAL DESCRIPTION

SIZE (width x length)	3" x 1000'
COLOR	Red, Yellow
ADHESIVE TYPE	Non-Adhesive
CONSTRUCTION	Single Coated
SELF WOUND	N/A
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	
WEIGHT	
Haze/Gloss	20%/40%

TECHNICAL DATA

ADHESIVE LAYER	N/A
BACKING/CARRIER MATERIAL	Polypropylene Film
BACKING/ADHESIVE THICKNESS	2 mil
TOTAL THICKNESS	3 mil
ADHESION TO STEEL	N/A
TENSILE STRENGTH	Break: 5000TD, 7000MD Yield: 1400TD, 1450MD
ELONGATION	400% + break point
TEMPERATURE APPLICATION	
TEMPERATURE OPERATING	

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com