

## DESCRIPTION

Durable Non-Skid Tape designed with a high traction grip surface to prevent injuries from slipping and falling. Consistent high slip resistance with silicon carbide 60 grit tape. High traction, waterproof, coated with an aggressive pressure sensitive acrylic adhesive.

## APPLICATION PROCESS

For indoor and outdoor use on pool areas, ramps, work areas, skateboards and garage steps. Comply with OSHA 1910.263 (3) and mil spec W-5044 Class II type IV

MATERIAL DESCRIPTION	
SIZE (width x length)	3" x 60'
COLOR	Black
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	Paper
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA	
ADHESIVE LAYER	Acrylic
BACKING/CARRIER MATERIAL	Paper
BACKING/ADHESIVE THICKNESS	N/A
TOTAL THICKNESS	6.1 mils
ADHESION TO STEEL	1500g/25mm
TENSILE STRENGTH	6.0 kg / 25 mm
ELONGATION	25% at break
TEMPERATURE APPLICATION	
TEMPERATURE OPERATING	23°F to 122°F Resistance

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210  
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996  
[can-dotape.com](http://can-dotape.com)