

DESCRIPTION

Brown Reinforced Gummed Tape. A light duty grade, reinforced water activated tape. Used in packaging and shipping applications to seal and repair boxes and corrugated cartons. Resists abrasion and wear experienced during shipping and distribution.

APPLICATION PROCESS

Sealing, closing and securing cartons/boxes in dusty or duty conditions. High grade kraft paper reinforced with strong fiberglass yarns. The adhesive is a smooth, even coating of special high tack, water-activated, modified cornstarch base.

MATERIAL DESCRIPTION	
SIZE (width x length)	3" x 450'
COLOR	Brown
ADHESIVE TYPE	Water-Activated Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA	
ADHESIVE LAYER	Gummed
BACKING/CARRIER MATERIAL	Kraft
BACKING/ADHESIVE THICKNESS	
TOTAL THICKNESS	5.0 to 7.3 mils
ADHESION TO STEEL	N/A
TENSILE STRENGTH	
ELONGATION	N/A
TEMPERATURE APPLICATION	N/A
TEMPERATURE OPERATING	

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com