

DESCRIPTION

Clear Polyethylene Film Tape. Single coated low density polyethylene film with rubber adhesive. Conformable, Good temp. characteristics. High adhesion and cohesion. Long term stability. Conforms well to irregular surfaces. Performs well at wide temperature range. Will not crack or crease at low temperatures. Custom slit to width

APPLICATION PROCESS

For general purpose sealing, splicing and seaming. Highly conformable. Abrasion, solvent, and moisture resistant. Excellent surface wettability. Conforms well to irregular surfaces. Stands up to mechanical and chemical wear. Adheres well to a variety of surfaces. Easy to apply. Adhesive will not fail after extended periods. Designed as a general purpose sealing, splicing, and seaming tape. Use as protective film and temporary hold down tape, material processing, and industrial fabricating applications.

MATERIAL DESCRIPTION	
SIZE (width x length)	36 yd
COLOR	Clear
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA	
ADHESIVE LAYER	Acrylic
BACKING/CARRIER MATERIAL	Polypropylene Film
BACKING/ADHESIVE THICKNESS	4.5 mil LDPE PSTC-133
TOTAL THICKNESS	5.5 mils PSTC-133
ADHESION TO STEEL	50 oz/in ASTM D-3330
TENSILE STRENGTH	11 lbs/in width ASTM D-3759
ELONGATION	400% at break
TEMPERATURE APPLICATION	50°F to 120°F
TEMPERATURE OPERATING	-40°F to 190°F

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com