

## DESCRIPTION

Double Coated Polyethylene Film Tape. A double coated polyethylene film tape with an aggressive rubber-base adhesive system. Designed with exceptional performance in applications where long term bonding is needed. Custom slit to width

## APPLICATION PROCESS

Ideal for mounting, cushioning, sound dampening, vibration, and for general industrial uses, such as mounting, adhering and bonding. Excellent carpet hold down application. Aggressive permanent adhesive bonds well to a wide variety of substrates including but not limited to carpet installation. Government specification conformance C.I.D A-A-1243B. Complies with FDA Code of Regulations, Title 21, Subpart B, Section 175.105. Code FDA 21CFR. Section 177.520, has cadmium chloride at 300-400PPM in the ink used for printing the release liner, but is certified.

MATERIAL DESCRIPTION	
SIZE (width x length)	36 yd
COLOR	White
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Double Sided
SELF WOUND	No
RELEASE LINER MATERIAL	Paper
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA	
ADHESIVE LAYER	Rubber
BACKING/CARRIER MATERIAL	Film
BACKING/ADHESIVE THICKNESS	1.5 mil
TOTAL THICKNESS	6.1 mils
ADHESION TO STEEL	50 oz/in
TENSILE STRENGTH	7.0 lb/in
ELONGATION	100% at break
TEMPERATURE APPLICATION	60°F to 120°F
TEMPERATURE OPERATING	-5°F to 140°F

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210  
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996  
[can-dotape.com](http://can-dotape.com)