

DESCRIPTION

Double Coated Polyester Film Tape. Double coated polyester adhesive tape (lined). Consists of a .5 mil polyester film coated on each side with a high performance water borne permanent acrylic based pressure sensitive adhesive and protected by a 78# BDK release liner. Custom slit to width.

APPLICATION PROCESS

Ideal for laminating to a wide variety of materials. It offers excellent general performance, good thermal stability and die cutting capabilities.

MATERIAL DESCRIPTION

SIZE (width x length)	36 yd
COLOR	Clear
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Double Sided
SELF WOUND	No
RELEASE LINER MATERIAL	Paper
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA

ADHESIVE LAYER	Acrylic
BACKING/CARRIER MATERIAL	Polyester
BACKING/ADHESIVE THICKNESS	.5 mil
TOTAL THICKNESS	2.3 mil
ADHESION TO STEEL	40 oz/in
TENSILE STRENGTH	N/A
ELONGATION	N/A
TEMPERATURE APPLICATION	55°F to 85°F
TEMPERATURE OPERATING	-20°F to 180°F

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com