

## DESCRIPTION

Double Coated Tissue Tape with a high tack synthetic rubber adhesive system. This is a lightweight tissue coated on both sides with a high tack, dead load synthetic-based adhesive system with an easy release polysilicone liner. It offers more strength than adhesive transfer tapes and is recommended in applications that require bonding of medium to heavy weight pieces of advertising, displays, forms and chipboard boxes. Excellent for use where a high degree of quick stick and exceptional peel is required. Custom slit to width.

## APPLICATION PROCESS

For use where a high degree of quick stick and exceptional peel is required. Particularly suitable for splicing because hand pressure is sufficient to transfer it. Hand tearable. Used for mounting nameplates, core start-up, mounting posters and signs, laminating to cork, cloth or felt, point of purchase displays, paper to paper applications, tag, ticket and label mounting, business forms, splicing papers, textiles, or plastics, permanent bag closure, board envelope and box fabrication and swatch application. This Double Coated Tissue Tape has a high tack and an excellent quick stick. It transfers easily to almost any surface and has a maximum bonding strength to eliminate product failure. Contains an extended liner for easy removal.

MATERIAL DESCRIPTION	
SIZE (width x length)	36 yd
COLOR	Natural
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Double Sided
SELF WOUND	No
RELEASE LINER MATERIAL	Paper
RELEASE LINER THICKNESS	2.5 mil
WEIGHT	

TECHNICAL DATA	
ADHESIVE LAYER	Rubber
BACKING/CARRIER MATERIAL	Paper
BACKING/ADHESIVE THICKNESS	1 mil
TOTAL THICKNESS	4 mil
ADHESION TO STEEL	80
TENSILE STRENGTH	10
ELONGATION	4
TEMPERATURE APPLICATION	0 to 180°F
TEMPERATURE OPERATING	

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210  
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996  
[can-dotape.com](http://can-dotape.com)