

DESCRIPTION

Clear Double Coated Acrylic Transfer Tape. Transfer tape consisting of a 2 mil acrylic pressure- sensitive adhesive on 60# Kraft release liner. Very easy unwind and removal of liner for ease of application. Very high quick-stick. Fast build-up of adhesion. Excellent holding power at elevated oven temperatures. Excellent adhesion to paper, plastic films, metal foils, etc. Adaptable to use in automatic tape guns. Custom slit to width.

APPLICATION PROCESS

Application of decorative parts, nameplates, envelope closure. Excellent adhesion to paper, plastic films, metal foils, etc. Adaptable to use in automatic tape guns. Our Double Sided Transfer Tapes provide durable, reliable and effective bonding, fixing and splicing.

| MATERIAL DESCRIPTION | |
|-------------------------|-------------------------|
| SIZE (width x length) | 55 yd |
| COLOR | Clear |
| ADHESIVE TYPE | Pressure-Sensitive Tape |
| CONSTRUCTION | Double Sided |
| SELF WOUND | No |
| RELEASE LINER MATERIAL | Kraft Paper |
| RELEASE LINER THICKNESS | 60# |
| WEIGHT | |
| | |

| TECHNICAL DATA | |
|----------------------------|---------------|
| ADHESIVE LAYER | Acrylic |
| BACKING/CARRIER MATERIAL | N/A |
| BACKING/ADHESIVE THICKNESS | 1 mil |
| TOTAL THICKNESS | 5.5 mil |
| ADHESION TO STEEL | 45 oz/in PSTC |
| TENSILE STRENGTH | N/A |
| ELONGATION | N/A |
| TEMPERATURE APPLICATION | min. 65°F |
| TEMPERATURE OPERATING | |

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com