

DESCRIPTION

Colored Multi-Purpose Duct Tape with versatile performance. Good balance of tensile strength and tearability. Good adhesion and tack. Conformable and will not twist or curl during application. Low residue. Custom slit to width

APPLICATION PROCESS

Excellent adhesion to a variety of surfaces. Aggressive adhesion to smooth and rough surfaces. General purpose repair. General purpose packaging. Sealing and closure tape for poly waste disposal bags. Hanging and seaming poly sheeting. Temporary holding and bundling. Bundling & securing carpets, padding and protective sheeting for the convention & hotel industry. General purpose abatement & contractor uses. Holding insulation materials in place. Condensation barrier in refrigeration assemblies. Color coding. Heavy duty box sealing. Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED. Low VOC Content.

MATERIAL DESCRIPTION

SIZE (width x length)	60 yd
COLOR	Olive Drab
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA

ADHESIVE LAYER	Rubber
BACKING/CARRIER MATERIAL	PE Coated Cloth
BACKING/ADHESIVE THICKNESS	N/A
TOTAL THICKNESS	9 mil ASTM D-1000
ADHESION TO STEEL	70 oz/in PSTC-101
TENSILE STRENGTH	24 lb/in ASTM D-1000
ELONGATION	20% ASTM D-1000
TEMPERATURE APPLICATION	
TEMPERATURE OPERATING	40°F to 200°F

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com