

DESCRIPTION

Clear Protective Film. Medium tack protection film. Custom slit to width

APPLICATION PROCESS

Temporary protective mask designed for use on textured and semi-smooth surfaces. Excellent for protection of polished #3 stainless steel, brushed aluminum, marble and similar surfaces. Allows for clean removal with minimal adhesion buildup.

MATERIAL DESCRIPTION

SIZE (width x length)	200 yd
COLOR	Clear
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA

ADHESIVE LAYER	Acrylic
BACKING/CARRIER MATERIAL	Film
BACKING/ADHESIVE THICKNESS	
TOTAL THICKNESS	3 mil PSTC-33
ADHESION TO STEEL	3.0 to 7.0 oz/in PSTC I
TENSILE STRENGTH	11 lb/sq in PSTC-31
ELONGATION	325% PSTC-31
TEMPERATURE APPLICATION	
TEMPERATURE OPERATING	

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com