

DESCRIPTION

PVC Industry Tape. Soft PVC tape suitably plasticized and stabilized. Coated with rubber-based pressure sensitive adhesive on one side. UPC Listed, matte finish industry tape. 100' Black Unprinted Pipewrap. Custom slit to width

APPLICATION PROCESS

For industrial identification, color coding and pipe wrapping purpose. It is moisture resistant, anti-corrosive and exhibits good adhesive to metal and plastic. Non-corrosive, pressure-sensitive adhesive eliminates the need of heat, moisture, or other catalysts to affect application.

MATERIAL DESCRIPTION	
SIZE (width x length)	100'
COLOR	Black
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA	
ADHESIVE LAYER	Rubber
BACKING/CARRIER MATERIAL	Soft PVC Vinyl
BACKING/ADHESIVE THICKNESS	N/A
TOTAL THICKNESS	9.8 mil ASTM D-1001
ADHESION TO STEEL	14.11 oz/in ASTM D-1001
TENSILE STRENGTH	19.8 lb/in width ASTM D-1001
ELONGATION	150% max at break ASTM D-1001
TEMPERATURE APPLICATION	under 140°F
TEMPERATURE OPERATING	under 140°F

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com