

## DESCRIPTION

Stretch Polyethylene Film - 80 Gauge. Standard duty stretch film. 18" x 1500'

## APPLICATION PROCESS

Cost-effective method for protecting palletized products through storage and distribution. Light weight for less operator fatigue and easy application. Reinforced edges for tear resistance & durability- no nicks, no frays, less waste. High puncture resistance. Good force to load holding power

### MATERIAL DESCRIPTION

|                         |                         |
|-------------------------|-------------------------|
| SIZE (width x length)   | 18" x 1500'             |
| COLOR                   | Transparent             |
| ADHESIVE TYPE           | Pressure-Sensitive Tape |
| CONSTRUCTION            | Single Coated           |
| SELF WOUND              | Yes                     |
| RELEASE LINER MATERIAL  | N/A                     |
| RELEASE LINER THICKNESS |                         |
| WEIGHT                  |                         |
| Dart Drop               | 76.3 g/mil              |

### TECHNICAL DATA

|                            |                           |
|----------------------------|---------------------------|
| ADHESIVE LAYER             | Film                      |
| BACKING/CARRIER MATERIAL   | Stretch Polyethylene Film |
| BACKING/ADHESIVE THICKNESS | N/A                       |
| TOTAL THICKNESS            | 0.80 mil                  |
| ADHESION TO STEEL          |                           |
| TENSILE STRENGTH           |                           |
| ELONGATION                 | MD: 600% / TD: 825%       |
| TEMPERATURE APPLICATION    |                           |
| TEMPERATURE OPERATING      |                           |

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210  
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996  
[can-dotape.com](http://can-dotape.com)