

DESCRIPTION

Stretch Polyethylene Film – 70 Gauge. Standard duty stretch film. 12" x 1500'

APPLICATION PROCESS

Cost-effective method for protecting palletized products through storage and distribution. Light weight for less operator fatigue and easy application. Reinforced edges for tear resistance & durability- no nicks, no frays, less waste. High puncture resistance. Good force to load holding power

MATERIAL DESCRIPTION

SIZE (width x length)	12" x 1500'
COLOR	Transparent
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	
WEIGHT	
Dart Drop	62.9 g/mil

TECHNICAL DATA

ADHESIVE LAYER	Film
BACKING/CARRIER MATERIAL	Stretch Polyethylene Film
BACKING/ADHESIVE THICKNESS	N/A
TOTAL THICKNESS	0.70 mil
ADHESION TO STEEL	
TENSILE STRENGTH	
ELONGATION	MD: 540% / TD: 850%
TEMPERATURE APPLICATION	
TEMPERATURE OPERATING	

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com