

DESCRIPTION

Reflective Tape. Engineer grade reflective tape. A high gloss reflective tape of high quality durable, enclosed lens retroreflective material. Offers exceptional value for permanent traffic signage applications. Custom slit to width

APPLICATION PROCESS

Rigid permanent and temporary outdoor signage. Rigid work zone devices. Non-essential signage where retroreflection is necessary. Field proven long term durability on safety devices worldwide. Pattern free face allows for clean graphic imaging. Economical choice for non-critical signs. Uniform daytime and nighttime appearance. Meets applicable requirements for engineer grade sheeting applications for Type I retroreflective sheeting as set forth in ASTM D 4956.

MATERIAL DESCRIPTION	
SIZE (width x length)	50 yd
COLOR	Silver
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	PE Coated Paper
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA	
ADHESIVE LAYER	Acrylic
BACKING/CARRIER MATERIAL	Paper
BACKING/ADHESIVE THICKNESS	N/A
TOTAL THICKNESS	N/A
ADHESION TO STEEL	N/A
TENSILE STRENGTH	N/A
ELONGATION	N/A
TEMPERATURE APPLICATION	40°F min
TEMPERATURE OPERATING	-40°F to 190°F

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com