

## DESCRIPTION

General Purpose Masking Packing Tape designed for packaging, bundling, holding and labeling for home, school and industry. Crepe paper, coated with rubber based natural pressure-sensitive adhesive. Economical, with good performance on variety of substrates. Good low temperature properties.

## APPLICATION PROCESS

Designed primarily as an all-purpose product for non-critical applications. Interior paint masking, silk screening, mail rooms, golf club shaft (build-up), school bids, and for light-duty bundling, packaging and tabbing. Applicable Standards: ASTM D 6123D/6123M-97, Type 1

### MATERIAL DESCRIPTION

SIZE (width x length)	Multiple Widths x 60 yd
COLOR	Natural   Tan
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	
WEIGHT	

### TECHNICAL DATA

ADHESIVE LAYER	Rubber base
BACKING/CARRIER MATERIAL	Crepe Paper
BACKING/ADHESIVE THICKNESS	N/A
TOTAL THICKNESS	5.1 mil (0.13 mm)
ADHESION TO STEEL	34 oz/in width (37 N/100mm width)
TENSILE STRENGTH	22 lbs/in width (385 N/100mm width)
ELONGATION	9%
TEMPERATURE APPLICATION	up to 150°F (66 c) for 30 minutes
TEMPERATURE OPERATING	

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210  
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996  
[can-dotape.com](http://can-dotape.com)