

## DESCRIPTION

Versatile Vinyl Tape, a soft PVC tape with an aggressive rubber-based pressure sensitive adhesive, in OSHA colors. Matte finished. Maintains color even with heavy abrasion. Residue-free removal. 36yd and custom slit to size.

## APPLICATION PROCESS

A “Do-it-all tape” for color codes, masks, seals, marking for hazardous or restricted areas. For industrial identification, color coding and duct wrapping. Ideal for floor or aisle marking. Conforms to curved and irregular surfaces. Non-corrosive, pressure-sensitive adhesive eliminates the need of heat, moisture, or other catalysts to affect application.

### MATERIAL DESCRIPTION

SIZE (width x length)	36 yd
COLOR	Grey
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	N/A
WEIGHT	

### TECHNICAL DATA

ADHESIVE LAYER	Rubber
BACKING/CARRIER MATERIAL	Vinyl
BACKING/ADHESIVE THICKNESS	N/A
TOTAL THICKNESS	6 mils ASTM D-1000
ADHESION TO STEEL	17.64 oz/in ASTM D-1000
TENSILE STRENGTH	16 lbs/in width PSTC-31 ASTM D-1000
ELONGATION	150% at break ASTM D-1000
TEMPERATURE APPLICATION	140°
TEMPERATURE OPERATING	Under 60 C (140 F)

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user’s method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210  
 p: 615.255.1775 • f: 615.256.6557 • 800.643.5996  
[can-dotape.com](http://can-dotape.com)